

HID Lamps

Lamps & Ballasts

Shape(s)



Base(s)



LB

HIGH PRESSURE SODIUM

Model #	Watts	MOL	Type	Base	Lumens	Avg. Life Hr	Operation Position	Rating	Finish	Color Temp	CRI	IP/MC
2H35HC	35	5.43"	ED17	E26	2200	14000	U	Enclosed	Clear	2000	20	12
2H50HC	50	5.43"	ED17	E26	3800	24000	U	Enclosed	Clear	2000	20	12
2H70HC	70	5.43"	ED17	E26	6000	24000	U	Enclosed	Clear	2000	20	12
2H100HC	100	5.43"	ED17	E26	9000	24000	U	Enclosed	Clear	2000	20	12
2H100MGHC	100	7.75"	ED23	E39	9000	24000	U	Enclosed	Clear	2000	20	12
2H150HC	150	5.71"	ED17	E26	15000	24000	U	Enclosed	Clear	2000	20	12
2H150MGHC	150	7.75"	ED23	E39	15000	24000	U	Enclosed	Clear	2000	20	12
2H250HC	250	9.76"	ED18	E39	28000	24000	U	Enclosed	Clear	2000	20	12
2H400HC	400	9.76"	ED18	E39	48000	24000	U	Enclosed	Clear	2000	20	12
2H1000HC	1000	15.08"	ED25	E39	120000	24000	U	Enclosed	Clear	2000	20	12

METAL HALIDE

Model #	Watts	MOL	Type	Base	Lumens	Avg. Life Hr	Operation Position	Rating	Finish	Color Temp	CRI	IP/MC
2M50HC	50	5.43"	ED17	E26	3200	10000	U	Enclosed	Clear	4000	65	12
2M70HC	70	5.43"	ED17	E26	5300	15000	U	Enclosed	Clear	4000	65	12
2M100HC	100	5.43"	ED17	E26	9000	15000	U	Enclosed	Clear	4000	65	12
2M100MGHC	100	8.11"	ED28	E39	9000	15000	U	Enclosed	Clear	4000	65	12
2M150HC	150	5.43"	ED17	E26	14000	15000	U	Enclosed	Clear	4000	65	12
2M175HC	175	5.43"	ED17	E26	14000	10000	U	Enclosed	Clear	4000	65	12
2M175MGHC	175	8.11"	ED28	E39	14000	10000	U	Enclosed	Clear	4000	65	12
2M250MGHC	250	8.11"	ED28	E39	21000	10000	U	Enclosed	Clear	4000	65	12
2M400EX39HC	400	10.94"	ED37	EX39	37000	10000	U	Open	Clear	4000	65	12
2M400MGHC	400	10.94"	ED37	E39	40000	20000	U	Enclosed	Clear	2600	65	12
2M1000MGHC	1000	10.94"	BT56	E39	110000	12000	U	Enclosed	Clear	4000	65	6
2M1500MGHC	1500	15.4"	BT56	E39	140000	-	U	Enclosed	Clear	4000	65	6



Sun Pacific Power
Building A Brighter Future...

**Sun Pacific
Power Corporation**
Phone: 888-845-0242
Fax: 732-845-2141
info@sunpacificpower.com

Lamps & Ballasts

HID Lamps

Shape(s)



ED37



ED28

Base(s)



E39

LB

PULSE START

Model #	Watts	MOL	Type	Base	Lumens	Avg. Life Hr	Operation Position	Rating	Finish	Color Temp	CRI	IP/ MC
2P250HC	250	8.11"	ED28	E39	25000	15000	U	Enclosed	Clear	2500	65	12
2P320HC	320	10.94"	ED37	E39	33000	20000+	U	Enclosed	Clear	4000	65	12
2P350HC	350	10.94"	ED37	E39	37000	20000+	U	Enclosed	Clear	4000	65	12
2P400HC	400	10.94"	ED37	E39	44000	20000+	U	Enclosed	Clear	4000	65	12



Sun Pacific Power
Building A Brighter Future...

**Sun Pacific
Power Corporation**
Phone: 888-845-0242
Fax: 732-845-2141
info@sunpacificpower.com

LB-15